

Product Data Sheet

GP LD TWIST GU10 3.1-35W W

	EAN	Packaging - SKU		
777886-LDCE1	4895149777886	Eco blister, 1 pc/SKU		
087427-LDB3	4895149087427	Colour gift box, 3 pc/SKU	11	
Product Category		LED Lampa		
Series		LED Lamps		
Model Series		REFLECTOR GU10		
		REFLECTORTWIST GU10	B. B.	
Description		GP LD TWIST GU10 3.1-35W 220-240V 36D		
General description	on		ø50	
Energy label		F		
Lamp shape		Reflector		
Lamp base		GU10	55	
Dimmable		No		
Mercury free Mercury content		Yes		
		0.0 mg		
•		Yes		
Recycling		res		
Electrical characte	eristics			
Nominal wattage		3.1 W ±10%		
Rated wattage		3.1 W		
Equivalent halogen lamp power		35 W		
Power factor		>0.5		
Voltage		220-240 V	Spectral Distribution	
Operating frequency		50/60Hz	Spectrum 1.0 = 6.652e*000mH/mm	
Lamp current		20-22 mA	1.0 = e.es2e=000m/mm	
-		20 22 110 1		
	eumption	4 KWh / 1000 h	1.07	
Weighted Energy Cor	nsumption	4 KWh / 1000 h		
		4 KWh / 1000 h	0.6-	
Weighted Energy Cor		4 KWh / 1000 h WARM WHITE	0.6-	
Weighted Energy Cor			0.8-	
Weighted Energy Cor Light technical ch Light colour Colour temperature	aracteristics	WARM WHITE	0.6-	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde	aracteristics	WARM WHITE 2700 K ±270K	0.6- 0.6- 0.4- 0.2-	
Weighted Energy Cor Light technical ch Light colour Colour temperature	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80	0.6-	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM	0.4- 0.2- 0.2- 0.35 45 45 49 740	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 lm ±10% 230 lm	0.6 - 0.4 - 0.2 - 0.2 - 0.0 -	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd	GP LED Reflectors are designed	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd	GP LED Reflectors are designed for true direct replacement of standard	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd ≥0.7	GP LED Reflectors are designed for true direct replacement of standard halogen lamps.	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominlal beam angle	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd ≥0.7 36°	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominlal beam angle Rated beam angle	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ≥0.7 36° 36°	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominlal beam angle Rated beam angle Warm-up time (60%)	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ≥0.7 36° 36° Instant	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominlal beam angle Rated beam angle	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ≥0.7 36° 36°	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Lumen maintenance f Nominlal beam angle Rated beam angle Warm-up time (60%) Starting time	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ≥0.7 36° 36° Instant	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light for different ambience	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Lumen maintenance f Nominlal beam angle Rated beam angle Warm-up time (60%) Starting time	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ≥0.7 36° 36° Instant <0.5s	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. With compatible shapes & sizes Very low energy consumption Extremely long life Emit a warm white or cold white light for different ambience Instant start with full light output	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Lumen maintenance f Nominlal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd cd 36° 36° Instant <0.5s	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light for different ambience	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominlal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time Rated lamp life time	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ⇒0.7 36° 36° Instant <0.5s	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light for different ambience • Instant start with full light output • No UV	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Lumen maintenance f Nominlal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time	aracteristics x (Ra)	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd cd 36° 36° Instant <0.5s	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light for different ambience • Instant start with full light output • No UV Applications	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominlal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time Rated lamp life time	aracteristics x (Ra) c factor at end of life	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ⇒0.7 36° 36° Instant <0.5s	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light for different ambience • Instant start with full light output • No UV	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time Rated lamp life time Switching Cycles	aracteristics x (Ra) c factor at end of life	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ⇒0.7 36° 36° Instant <0.5s	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light for different ambience • Instant start with full light output • No UV Applications • Domestic and commercial applications • General illumination	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time Rated lamp life time Switching Cycles Product dimensio Overall length (L)	aracteristics x (Ra) c factor at end of life	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd ≥0.7 36° 36° Instant <0.5s 15000 h 15000 h 50000	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. With compatible shapes & sizes Very low energy consumption Extremely long life Emit a warm white or cold white light for different ambience Instant start with full light output No UV Applications Domestic and commercial applications General illumination Can be used everywhere at home	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time Rated lamp life time Switching Cycles	aracteristics x (Ra) c factor at end of life	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ≥0.7 36° 36° Instant <0.5s 15000 h 15000 h 50000	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. • With compatible shapes & sizes • Very low energy consumption • Extremely long life • Emit a warm white or cold white light for different ambience • Instant start with full light output • No UV Applications • Domestic and commercial applications • General illumination	
Weighted Energy Cor Light technical ch Light colour Colour temperature Colour rendering inde Colour consistency Nominal luminous flux Rated luminous flux Rated peak intensity Luminous intensity Lumen maintenance f Nominal beam angle Rated beam angle Warm-up time (60%) Starting time Lifespan Nominal life time Rated lamp life time Switching Cycles Product dimensio Overall length (L)	aracteristics x (Ra) creator at end of life	WARM WHITE 2700 K ±270K >80 <6 SDCM 230 Im ±10% 230 Im cd cd cd ≥0.7 36° 36° Instant <0.5s 15000 h 15000 h 50000	GP LED Reflectors are designed for true direct replacement of standard halogen lamps. With compatible shapes & sizes Very low energy consumption Extremely long life Emit a warm white or cold white light for different ambience Instant start with full light output No UV Applications Domestic and commercial applications General illumination Can be used everywhere at home Use outdoors only in enclosed and	

www.gp-lighting.com