

Product Data Sheet GPACLLTFN000

Order code	EAN	Packaging - SKU	
GPACLLTFN000	4895149085522	Eco blister, 1 pc/SKU	
			11-1
Product			
Category		LED Lamps	
Series		DOMESTIC REFRIGERATORS/DECO	
Model		GPACLLTFN000	
Description		GPLTFN2525B-2U1/085522-LD,	
		T25 E14 2.5-25W 220-240V CL FM	
General description	1		
	•	E	
Energy label			U. 197
Lamp shape		T25	E-81
Lamp base		E14	三宝
Dimmable		No	23
Mercury free		Yes	
•			923
Mercury content		0.0 mg	
Recycling		Yes	
Electrical character	ristics		
Nominal wattage		2.1W	
Rated wattage		2.1W	
Equivalent incandescen	nt lamp power	25W	
Power factor	icanip power	0.4	Spectral Distribution
			Spectral Distribution
Voltage		220-240V	
Operating frequency		50Hz	Spectrum 1.2
Lamp current		25 mA	0.8
Weighted Energy Cons	umption	3	0.6
light tooksissisis	ractorictics		0.4
Light technical characteristics		WARM WHITE	0.2
Light colour		2700 K ±270K	0.0
Colour temperature Colour rendering index	(Pa)	80	- 300 460 560 680 780 Wavelength (nm)
	(Na)	6	
Colour consistency Nominal luminous flux		250	
Rated luminous flux		250	GP LED Lamps are designed for
kated luminous flux Lumen maintenance fac	ctor at end of life	0.7	true direct replacement of standard
Nominial beam angle	a.c. a. ona or me	360°	and another representation of standard
Rated beam angle		360°	
Warm-up time (60%)		instant	incandescent lamps.
Starting time		<0.5s	Compatible shapes and sizes of GLS
		, r	Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000h	Emit a warm white or cold white light
Rated lamp life time		15000h	for different ambience
Switching cycles		50000	Instant start with full light output
'			Available in most common lamp bases
Product dimensions			for household use
Overall length (L)		85	• No UV
Diameter (D)		25	
			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
* Please refer to website www.gp-lighting.com for the list of compatible dimmers.			Can be used everywhere at home
			Use outdoors only in enclosed and

www.gp-lighting.com